







---

Panasonic Manufacturing Philippines Corporation (PMPC)

 [www.panasonic.com/ph](http://www.panasonic.com/ph)  
 [facebook.com/PanasonicPhilippines](https://facebook.com/PanasonicPhilippines)  
 [@panasonic\\_ph](https://www.instagram.com/panasonic_ph)  
 [@panasonicph](https://twitter.com/panasonicph)  
 [pmpe\\_csdcc@ph.panasonic.com](mailto:pmpe_csdcc@ph.panasonic.com)

**Panasonic**<sup>®</sup>

GET TO KNOW MORE  
ON OUR SOLUTIONS



JOIN OUR GROWING  
COMMUNITY



---

Specifications are subject to change without notice.

**Panasonic**

**b2b solutions**



**CONTROL**  
Solutions



**SAFETY**  
Solutions



**SAVINGS**  
Solutions



**SECURITY**  
Solutions



**COMFORT**  
Solutions

**TOTAL  
INTEGRATED  
SOLUTIONS**

FOR EVERY BUSINESS NEEDS





# Create Today, Enrich Tomorrow with **Panasonic**

Experience better living at home, at work, or whatever life takes you. Panasonic's total solutions are designed to improve all aspects of your life combining different products to provide the best fit for your Control, Safety, Savings, Security, and Comfort needs.



## **CONTROL** Solutions

Eases accessibility with standard and smart control devices.



## **SAFETY** Solutions

Products and Systems that provides safety for your home and family.



## **SAVINGS** Solutions

Reduction on energy consumption through efficient products and systems.



## **SECURITY** Solutions

Monitor and secure your properties from any unwanted incidents.



## **COMFORT** Solutions

Achieve better lifestyle upgrades with products that improves your well being.

# OVERVIEW

Widely known as the electronics giant in the consumer electronics industry, Panasonic has come a long way to brand itself as one of the market leaders and has since evolved from attachment plugs to integrated solutions. Today, the major contributor to the company's total business is the B2B sector, while its B2C plays a smaller yet important role.

Japan has been at the forefront of the "Smart & Sustainable" house trend and Panasonic is one of the companies which has been active in this field. The recent economic growth spurt in Asia has led to the rise in demand for higher quality living, and this has challenged Panasonic to pioneer energy-efficient products and smart automated systems for the region.

The changing landscape of homes in Asia, coupled with a growing interest in sustainable living and concern for the environment by consumers in the region, has inspired the company to develop technologies that cater to these needs.

This publication is a convenient reference of our technologies, and includes everything from systems for the household, state-of-the-art smart houses to the Internet-of-Things. Panasonic has it all.

As a company that works to understand and adopt the culture of each country, we will continue to innovate, to create the future with our consumers in the areas of Residential and Non-Residential.



# PANASONIC CASE STUDIES

## Application of Total Panasonic Solutions to Different Project Types

Residential Solutions	01
Exterior & Interior	
Hotel Solutions	02
Suite Room	
Conference/Ballroom	
Commercial Solutions	03
Market	
Parking	
Storage	
Restaurant Solutions	04
Diners	
Quick Service Restaurants	
Industrial Solutions	05
Factory	

## CONTROL SOLUTIONS

Panasonic Control Solutions Overview	06
--------------------------------------	----

### STANDARD CONTROLS

Switches	07
Slim Art	
Flatima Series	
Refina Full Color Wide Series	
Timers	08
Automatic Time Switch	
Sensors	09
Passive Infrared Sensor	

### SMART CONTROLS

Home Automation	10
Thea IQ Home Automation System (KNX)	
Building Automation	11
VRF Smart Connectivity	
Information	
Interactive Kiosk	14
Smart Projector Control	15
Smart Food Locker	16
Flat Panel Displays	17
Video Wall Displays	18
Projector	19

## SAFETY SOLUTIONS

Panasonic Safety Solutions Overview	20
-------------------------------------	----

### HOME SAFETY

Electrical Protection	
Miniature Circuit Breaker	21
MCB Panel Boxes	23
Outlet with Switch	24
Electrical Protection	
Earth Leakage Guard (GFCI)	26
Structural Quality	
Ventilating Fan	27

### FAMILY SAFETY

nanoe™ Technology	
Air-Conditioner	31
Air Quality Solutions	32



## FAMILY SAFETY

Air-E	33
Bidet	
Electric Bidet	34

## SAVINGS SOLUTIONS

Panasonic Savings Solutions Overview	35
--------------------------------------	----

### PASSIVE SAVINGS

Direct reduction on energy consumption	
Solar Panel	36
LED Fixtures	37

### ACTIVE SAVINGS

Reduction which depends on usage	
Floor Standing Air-Conditioner	38
Ceiling Fan	39
LED Dimmer Switch	40
VRF Air-Conditioner	41
Commercial Refrigerator	42
Inverter Condensing Units	43
R32 Multi-Split Air Conditioning System	44
Energy Recovery Ventilator (ERV)	45
Multi-Split Outdoor	46
Econavi	47

## SECURITY SOLUTIONS

Panasonic Security Solutions Overview	49
---------------------------------------	----

### STAND ALONE

Fire Protection	50
Smoke Alarm	
Property Protection	51
Auto Door System	
Door Hardware and Accessories	

### INTEGRATED SYSTEMS

Fire Protection	
Fire Detection and Alarm Systems	53
Property Protection	
IPro Series Security Cameras	54
Video Intercom System	55

## COMFORT SOLUTIONS

Panasonic Comfort Solutions Overview	56
--------------------------------------	----

### WELLNESS

LED TV	57
Bathroom Water Heater	58
Hair Dryer	59

### HOME IMPROVEMENT

Electric Iron	60
Cordless Vacuum Cleaner	61
Professional Microwave Oven	62
Single-Door Refrigerator	63
No-Frost Deluxe Refrigerator	64

# I N D E X



# Application of **Panasonic Solutions**


TO DIFFERENT PROJECT TYPES

---



## Exterior






## Interior















## Factory



## BMS





# Control Solutions

Eases accessibility with standard and smart control devices.

## Applications

RESIDENTIAL

RESTAURANTS

SCHOOLS

OFFICES

HOSPITALS

STORES

FACTORIES



Our extensive range of control systems are the answer to every project and application. From standalone units to centralized control systems, Panasonic continues to lead the way in control and connectivity.

## Key Factors




Applicable to new and renovation projects.



Cost efficient and low maintenance.



Easy to operate and user-friendly interfaces.



# SlimArt SWITCHES & PLATES

New Slim Designs to Harmonize with Any Living Space



## SLIM WITH SNOW WHITE COLOR

Provides a softly lit LED indicator for easy visibility in the dark.



## SOFT-TOUCH OPERATION & WIDE SWITCH

Advanced switch mechanism offers smoother ON/OFF switching.



## ACHIEVING SAFETY THROUGH RELIABILITY

Made of a material that resists color fading even when constantly bathed in room light or sunlight.

# REFINA FULL-COLOR WIDE SERIES

Wide color range suits modern interiors

FULL - COLOR WIDE SERIES REFINA A - TYPE

Various Combination : 7 Plate Colors X 7 Switch Colors




White W Metallic White MW Metallic Gray MG Metallic Black MB Metallic Gold MY Metallic Brown ME Metallic Dark Brown MA

The last 2 characters in  of Refina product numbers show the item color.

# V-HOTEL SERIES

Perfect fit for modern interiors.

SLEEK & SLIM PLATES  
MATCHING MODERN INTERIORS




6mm-thin plate matches with modern interior styles,

LIGHT TOUCH FEEL DESIGN  
LED INDICATOR



Advanced switch mechanism enables soft touch operation with less noise and trouble. Electricity can be confirmed in one look with LED indicator

NAMING OPTION  
CUSTOMIZED HOTEL NAME



For a special project, we can offer special print on the product like project name, any original character, etc.





**CONTROL**  
Solutions

## AUTOMATIC TIME SWITCH

Available in a wide variety of models to suit  
a multitude of environmental and weather conditions.



## What's an Automatic Time Switch?

An automatic time switch automatically controls the use of electricity according to time. It's a device that lowers both electrical and labour costs.

### Automatically Turns the Power On and Off

The Time Switch combines a clock with a switch to automatically turn power on or off at preset times. It is generally built into a lightboard or distribution panel, and controls electricity on a 24-hour. It makes it possible to replace conventional manual control with automated, reliable ON/OFF time management.

### Eliminating Electrical Waste is Also Ecological

Because the power is reliably turned on and off according to a preset time schedule, the amount that was wasted by extended use is saved, and electric bills are effectively lowered.

### Cutting Labor Costs Is Also Efficient

Since the job of turning the power on and off is done automatically instead of manually, you can assign your valuable human resources to more important jobs. Human error is also eliminated, so power management is more reliable.

### Simply Set the Time for ON/OFF Control


Time management consists of simply setting the times to turn the power on and off. A wide range of uses are possible across various operations, such as lighting, air conditioning, water supply, and livestock feeding.

#### Example: Managing electricity in the office




**From 1:00 PM - 6:00 PM**

Lighting and air conditioning are turned on precisely when lunchtime ends. Then the power is automatically turned off when the workday finishes. Again, no power is wasted.



**From 12:00 PM - 1:00 PM**

Lunchtime. Lighting and air conditioning are turned off while people leave the office for lunch. No power is wasted.



**From 8:30 AM - 12:00 AM**

Turn the power on at the start of the workday. Lighting and air conditioning are turned on to provide a smooth start to office work.






New innovation with  
New energy-saving lighting control

# PASSIVE INFRARED SENSOR

**Best for Energy saving and Touchless demand.**  
Sensing human motion and automatically turn On/Off the lights.

## Demonstration



## Features

### Non Contact

PIR Sensor reduces the risk of contact infection because it automatically turns ON/OFF the light **without touching the switch** at toilet and meeting room etc.

### Safety

PIR Sensor automatically turns ON/OFF the light without exploring switch in a dark area.

Rest assured that the elderly and children **will not stumble**.

### Energy Saving

PIR Sensor automatically turns ON/OFF the light in case of no people in the warehouse and it leads to power saving.

**PaPIRs PIR Sensor**

Made in JAPAN

High sensitive quad pyroelectric element

Original designed ASIC

**PaPIRs provides higher "Sensitivity" and "Reliability"!**  
Reliable detection when small temperature difference between the ambient temperature and the target object.

- **2 Times better Sensitivity**  
-Slid design elements prevent thermal crosstalk between the single sensing elements.
- **4 Directions detection**  
-Improve detection performance with Quad elements.
- **4 Times better signal-to-noise ratio**  
-Original designed ASIC decrease the probability of false alarms  
-Fine tuned detection setting in ASIC with our knowhow

**Conventional PIR**  
-Dual element

**PaPIRs element**  
-Quad element with slit design

**Thermal crosstalk**


**2-way direction detection** vs **4-way direction detection**

**Analog output diagram**

**Conventional PIR sensor** vs **PaPIRs**


**False alarm**

## Recommended Location




**Multiple detection as Saving cost.**  
**Suitable for hallway and parking.**

Inter-connectable type



Number of Auxiliary units connected; WTKG2411[3A] 4 units, WTKF24816-PH[8A] 6 units

## Wiring Method



## Adjustable Lens

Adjusting detection area up to 15°C in any direction. Possible to change required detection area after installation.



**When it can't be installed in the required position**

When a sensor can't be installed in the required position due to Lighting or Fire alarm.

Up to 15°

**When changing detection area**

When changing sensing position as approaching closer/further to a sensor.








## Smart Building Functions

Manage your smart building remotely if you wish.

In home, office spaces, galleries, and general sites, you can centrally manage all of the smart home / smart building / automation functions from a single point. Control points can be located in the screen as a sketch, a picture of the location, or a grid.

Therefore, a user-friendly interface provides ease of use for all ages. All of these functions can be utilized even from a distance through your mobile phone.

- Illumination
- Dimming
- Curtain
- Shutter
- Thermostat
- Alarm
- Security







## Connect to the Future **VRF Smart Connectivity+** ~New SE8000~




Through thorough energy management, Panasonic's VRF Smart Connectivity is a completely new, state-of-the-art solution providing energy saving and comfort as well as simple installation, operation, and running.



### **Quality Air Control**

Optimum IAQ is realized using the CO<sub>2</sub> & humidity sensors. The interior remains comfortable, while heating and cooling costs are minimized. The CO<sub>2</sub> sensor controls ventilation systems which contributes to improving the room's air quality.



### **Room Key Card or Key Cardless Solutions for Hotels**

Solutions are provided that meet the needs of various regions and hotel grades. While the previous model's automatic detection function offered optimal air conditioning with or without a hotel room key card, the latest model enables conventional key cards to control air conditioners and other devices coordinately. The increase in the types of devices that can be connected enables customized control of any hotel room.



### **Other Equipment Control**

One room controller manages various devices including lighting and the blinds. A ventilation system and other external connection devices (dry contact input) can be connected so that various control is possible with this controller alone, even without BMS.



## Color and Design to Match Office Interiors

Color combinations and design can be set to match different facilities.



## Customization in Approx. 22 Languages Possible

The display can be customized to match the native languages of guests to enable smooth, stress-free communication for hospitality at its finest.



## Easy-to-Understand Error Description

Error description during an emergency is easy to understand, enabling staff to respond quickly.



## Programmable Logic

Full customisation of remote control logic possible, and updating to match conditions.

## Features

- Up to 5-year battery life batteries included (CO<sub>2</sub> sensor is 10 years)
- Battery level is a point
- Sensor points visible when SE8000 is integrated via BACnet MS/TP
- Sensor status and battery level visible when SE8000 is integrated via ZigBee® Pro


Note: With optional VCM communication card



ZigBee®  
Communication Card  
VCM



Schneider Electric  
brand - SE8000



## ENERGY MANAGEMENT SYSTEM FOR ROOMS

By installing a walVceiling motion temperature sensor, window/door sensor, and CO2 sensor in the room, ideal, waste-free air conditioning is achieved.

## SENSING AND CONTROL TECHNOLOGY

Using sensors from Schneider Electric, high-quality - occupancy control and automatic IAQ control are realized. The sensors detect the presence or absence of occupants, and the opening and closing of doors and windows to achieve the most efficient energy management for exceptional air-conditioned comfort.

Flexible installation is possible to match different applications and building features such as walls, ceilings and proximity to doors and windows. No wiring means extra installation versatility.

Batteries last for up to five years (10-year battery for CO<sub>2</sub> sensor) and are easy to install and replace.



Pana Net Con, RH, No PIR, SE Brand, R1R2  
SER8150R0B1194

Pana Net Con, RH, PIR, SE Brand, R1R2  
SER8150R5B1194



Wireless ZigBee® Pro communication card  
VCM8000V5094P



Hotel room expansion module 14 indoor units  
HRCEP14R



Hotel room controller 28 indoor units  
HRC PBG28R



Hotel room controller w/display 42 indoor units  
HRCPDG42R

\* Those accessories require system integrator support on site.



Sensor with room CO<sub>2</sub>,  
temperature and humidity  
SED-CO2-G-5045



Sensor with room temperature  
and humidity  
SED-TRH-G-5045



Door/window sensor



Wall/ceiling motion/temperature/  
humidity sensor  
SED-MTH-G-5045



**Water leakage sensor**  
SED-WLS-G-5045



Cover frame - Silver  
FAS-00

Cover frame - White  
FAS-01



Cover frame - Glossy translucent white  
FAS-03



Cover frame - Light tan wood  
FAS-05



Cover frame - Dark brown wood  
FAS-06



Cover frame - Dark black wood  
FAS-07



Cover frame - Brushed steel finish  
FAS-10

Up to 5 years battery life (batteries included). Battery life of CO<sub>2</sub> sensor up to 10 years. Battery level data point.





**CONTROL**  
Solutions


K865 15" | KOT21 21.5" | KOT32 32" | KOT43 43" | KOT55 55"

## Interactive KIOSK



### Better customer experience with Panasonic Interactive Kiosks.

Panasonic Interactive Kiosks has different types and sizes that cater to different industries with different applications depending on the requirement of the client. It is customizable, easy to operate, and has many provisions that can be modified.




Help re-deploy the workforce to smarter customer retention



Allow customers to engage directly with the ordering system to ensure they get what they want.




Provide faster service to increase table turnover.



The integrated content designing tools help to create a truly unique experience for customers.

# Smart Projector Control

Smart Projector Control is a smartphone application that enables various controls, from turning the power on and off to various lens adjustments.



Download Smart Projector Control (free) from App Store or Google Play.

## ADVANTAGES

- The projector can be set and operated from a smartphone application, so there is no hassle associated with the remote control or main body buttons.
- Multiple projectors\* can be operated simultaneously, and the status of a selected projector can be checked.  
\* Up to 64 projectors can be registered.
- A detailed screen of projectors registered in Early Warning Software can be displayed.

## Geometric Adjustment Feature and Upgrade Kits Expand Projection Capability

Flexible projection with a peripheral system turns image viewing into a memorable experience. Panasonic offers features that provide truly unique applications.

### Geometric Adjustment (free)

Projectors with a built-in Geometric Adjustment function expand projection capability onto spherical, cylindrical, and other specially shaped screens.

### Geometry Manager Pro Software & Upgrade Kit (for a fee)

Using this software allows you to perform real-time geometric compensation and other fine adjustments and corrections that cannot be handled on the projector side.



## Wireless Projector for Android



Download Panasonic Wireless Projector (free) from Google Play.



The AJ-WM50 is the dual band, compact wireless module for P2HD and AG-DVX200 camera recorders.

The WM50 dual band (2.4GHz and 5GHz) makes for a more reliable, stable connection to a network in various environments yet its compact size enables it to fit in the wireless module compartment of the P2HD cameras. 2.4GHz offers strong connection through obstacles and compatible with many devices whereas 5GHz offers stability from radio wave interference (Microwave, Bluetooth, etc.)

### Key Features

- Compact size, fits inside camera body same as WM30
- Dual Band 2.4GHz and 5GHz (IEEE802.11 a/b/g/n/ac compliant)
- High security WPA2-PSK (TKIP/AES) WPA-PSK (TKIP/AES) WEP (64bit/128bit)

#### Displayable Content


- JPEG/PNG files
- PDF files
- Camera (camera equipped devices only)
- Snap Shot

#### Marker Function



[Blackboard mode\*5]

#### Multi-Live Mode



#### Web Control Function




#### Browser Remote Control Function






# Smart Food Locker

Smart Locker technology from Panasonic provides guests with an easy and secure option to pick up off-premise orders at peak freshness, all in a dedicated space.



**COLD**



**HOT**



**AMBIENT**



## THE NEXT GENERATION OF TAKE-OUT ORDERING

Panasonic provides the latest technology in meals to go, which offers the ability for a customer to order and pre pay through a mobile app or stationary ordering kiosk. The cubby wall is available with rear or front loading, where the system software selects the appropriate cubby that can be hot, cold, or ambient. Once the cubby is loaded, a code can be sent to the customer which will direct them to their designated cubby. It can then be easily opened for order pick up.

• **CUSTOMIZABLE COLOR**

• **MODULAR DESIGN**



### EASY TO ADD INTO YOUR EXISTING SPACE

Install in a restaurant or communal space and create a dedicated area for take-out orders



### CUSTOMERS CAN ONLY ACCESS THEIR SPECIFIC LOCKER

Smart Lockers can only be opened by the customer with the corresponding order code. Simply scan the code and your locker will open




### A SEAMLESS INTEGRATION

Smart Food Locker hardware integrates with your native ordering system, as well as popular app-based delivery platforms

## 3 EASY STEPS

- 1 LOCKER IS LOADED**  
Restaurant's runner loads the food locker unit with an order and assigns the locker to the corresponding customer
- 2 CUSTOMER IS ALERTED**  
Panasonic's custom-tailored software notifies the customer their order is ready and provides locker access instructions
- 3 UNIT IS UNLOCKED**  
Upon arrival, the customer enters the code provided in the locker access instructions and is able to retrieve their food

## CONTACTLESS CARRY OUT SIMPLIFIED






# FLAT PANEL DISPLAY

TH-98SQ1 | TH-43SQ2H | TH-55SQP1


## Stylish, simple and flexible digital signage displays

Versatile flexibility in a sleek, slim design, these displays offer stunning images in a variety of sizes up to 84-inch, with appealing narrow bezel, wide-viewing angle and built-in USB media player.



## EQ2 Series

TH-75EQ2W; TH-65EQ2W; TH-55EQ2W; TH-50EQ2W; TH-43EQ2W



### Key Features


- Easy to connect peripherals (camera/speaker) directly to display
- Increased input type and number of available inputs
- Function slot for increased functionality
- Higher visibility due to brightness typically found on higher end products
- Installation flexibility – portrait and tilt supported

### Key Features

- High image quality and high legibility suitable for various scenes
- Superb Reliability & Easy Installation
- Various external linkage suitable for conference room and signage applications



## SQP1 Series



500 cd/m², 4K IPS (panel with slim and stylish design and 24/7 operation).

### Key Features

- High image quality through HDR support (HLG system) that displays light and dark images in a realistic way
- 4k USB Media P.layer: eliminates the need for external devices and allows updates via LAN.
- High expandability with ultra-slim Intel® SDM (Intel® Smart Display Module), Display Port connection for daisy-chain signage, multiple screen function (quad, PinP, PbyP) and 4K DIGITAL LINK
- Flexible and light installation either in portrait or landscape.



## Unique feature of EQ2 Series

### • Built-in Whiteboard (Mouse Annotation)

Able to write onto the display screen out with the mouse. You can also zoom the screen by scrolling the mouse wheel.



### • USB Pass Through

USB devices can be connected to the display via a USB-A cable and controlled using a PC connected to the EQ2 via the USB-C port.



Education

Corporate

Museum/Exhibits

Transportation

Advertisement

Showrooms

Entertainment

Digital Menu Boards




# Video Wall Display



## Stop audiences in their tracks.

An ideal solution to create large engaging video walls with an ultra-thin narrow frame and usage in digital signage, broadcast and control rooms.



## VF SERIES

The VF Series delivers seamless, multi-screen Display for dynamic, large-screen use.

### TH-55VF21



### TH-55VF31



## Key Features (TH-55VF2 & TH-55VF2H)

- Durable panel material and quality components ensures dependable 24 hours operation seven days a week
- Ultra narrow bezels on the VF31 series video wall reduce bezel-to-bezel distance to a near-invisible 0.88mm

MODEL	TH-55VF31	TH-55VF21
SCREEN SIZE	55-inch	55-inch
BRIGHTNESS	500cd/m <sup>2</sup>	500cd/m <sup>2</sup>
PANEL TYPE	IPS / Direct-LED	IPS / Direct-LED
PANEL SURFACE TREATMENT	Anti-glare (Haze 28%)	Anti-glare (Haze 28%)
OPERATING TIME	24 h/day	24 h/day
RESOLUTION	1920 x 1080	1920 x 1080
BEZEL TO BEZEL	0.88mm	1.8mm



**Railway & Traffic Management**



**Control Room**




**Museum and Exhibits**



**Advertisement & Transport**



**Schools and Corporate**



**Showroom and Virtual Windows**



# Projectors

## Absolute Brilliance

Create engaging experiences with bold, bright, vivid visuals. No matter the venue or size of your audience, our range of projectors will help your creative vision come to life.



### PT-REQ15

1-Chip DLP™ Projectors 4K Laser Projector



Designed to streamline productions and expand the endless possibilities of entertainment by delivering exceptional, highly engaging immersive experiences with up to 12,000lm brightness, 4k resolution and 240 Hz projection capability




### PT-REZ15

1-Chip DLP™ Projectors



Transform Your Experience with Evolved 1-Chip DLP™ Projectors, Delivering Up to 15,000 lm on AC 100–240 V



Model	PT-REQ15	PT-REZ15
Light Output <sup>4</sup>	15,000lm	
Dimensions (W x H x D)	W/out lens 498 x 212 x 538 mm (19 5/8" x 8 11/32" x 21 3/8") (W/ feet at shortest position)	
Weight	W/out lens: Approx.27.0 kg (59.52lbs)(TBD)	
Resolution	4K (3840 X 2400 px) <sup>1</sup>	WUXGA
Operation noise <sup>2</sup> Normal/Quiet	42 dB(38dB)(TBD)	

#### Key Features

##### ● Spectacular Visual

- Smooth, and Dimensional 4K<sup>1</sup> Images
- Deep image with evolved Dynamic Contrast
- Smooth Playback of 2K/240 Hz<sup>3</sup> Content

##### ● Effortless Workflow

- Full brightness on AC100-240V
- Wide Scalability with Intel® SDM-ready Slot
- Works with new lens lineup featuring wider lens ,shift range, all motor driven (powered periphery focus added)

##### ● Reliable Operation

- Optical engine and laser light source module compliant with the IP5X Dust Protected (IEC 60529) standard
- Remote Preview LITE for Monitoring During Events
- Backup input, Multi-Laser Drive Engine for reliable operation

1 REQ15 only. With Quad Pixel Drive [ON]. 2 Only when optional TY-SB01DL DIGITAL LINK Terminal Board is loaded. 3 PT-REQ15 only. Supports input signals up to 1080p. The display frame rate corresponds to the input signal frame rate.4 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is the average of all products when shipped.

### PT-RQ35K

Large Venue

Deliver More for Less with the World's Smallest and Lightest 20,000lm 3-Chip DLP™ 4K Laser Projector



#### Key Features

- Compact Form-Factor Streamlines Workflow
- Create an Engaging Visual Experience
- Reliable and Maintenance-free for Peace of Mind
- Dome Mapping; Theme Park, VR Simulation



### PT-VMZ1


Portable Laser Projector

Delivers Up to 7,000 lm for Clear, Vivid Images in Well-Lit Classrooms and Offices.



#### Key Features

- High brightness from light and compact body
- Flexible installation adapts to any space
- Smooth and effortless collaboration



### PT-CMZ50


Ultra Short Throw

Laser Projector Delivers Big Pictures from Ultra-Short Distances (1 cm)



#### Key Features

- Delivers 80-inch image from about 1 cm
- Simplified Installation, Setup, & Adjustment
- Wireless Projection



### PT-MZ20K

Installation

The World's Smallest, Lightest, and Quietest 20,000 lm1 Projector



#### Key Features

- Compact but with high brightness and vividness
- High reliability & energy-saving design
- Simplified Installation with enhanced functions







**SAFETY**  
Solutions



# Safety Solutions

Products and Systems that provide safety for your home and family.

## Applications

RESIDENTIAL

RESTAURANTS

SCHOOLS

OFFICES

HOSPITALS

STORES

FACTORIES

Ensure safety of your family and property with our products developed to provide utmost protection featuring technologies that are carefully chosen and certified as recommended by industry professionals.

## Key Factors



Applicable to new and renovation projects.



Provides total safety solution for different applications.



**SAFETY**  
Solutions



Safe and comfortable life  
Delivered by Panasonic

## Miniature Circuit Breakers

**Safe and comfortable life delivered by Panasonic**

Panasonic, with more than 100 years of expertise forged in the Electrical Construction Material field with its Wiring Devices series, has also been expanding Switchgear devices business throughout the world. Panasonic focuses on providing high durability and performance for many years of reliable use, and selects materials with full consideration of the global environment. Certification by third-party institutions and compliance with a wide range of international standards attest to these efforts. This approach is also used with Panasonic's MCBs, to allow our worldwide customers to experience a new level of safety and comfort in your life.




### Adequate Line-Up


Rated breaking capacity (Icn): 4.5kA / 6kA / 10kA  
Rated current (In): 6, 8, 10, 13, 16, 20, 25, 32, 40, 50, 63A  
Thermo-magnetic release characteristic: B / C / D

### Clear Indicator


Current markings indicated by 2 colors (Green / Red)  
Easy to know the status (ON / OFF)



On : Red



Off , Trip : Green



IEC60898-1  
IEC61008-1  
IEC61009-1

### Compliant with IEC standards

Panasonic's products have been recognized and certified by worldwide famous organizations as the complied products with IEC (International Electrotechnical Commission) standards, the top reference for electrical and electronic safety standards.

### Compliant with the RoHS Directive

Panasonic's manufacturing processes are based on management standards for chemical substances by complying with the EU RoHS directive in order to provide all of our customers safer products with less impact on the environment.

**RoHS**  
Compliant

Compliant with the RoHS Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment.






## THE TRIPPING MECHANISM OF MCBs is THERMAL MAGNETIC TYPE

### Thermal operation

- The thermal operation provides protection from moderate overloads. Under overload condition, a thermo-metallic element (bimetallic strip) deflects until it operates a latching mechanism allowing the main contacts to open.

### Magnetic operation

- In magnetic operation, large overloads or short circuit current actuates a solenoid causing a plunger to strike the latching mechanism, rapidly opening the main contacts.




- |                      |                          |                               |
|----------------------|--------------------------|-------------------------------|
| ① Operating Knob     | ⑥ Arc Chute Plate        | ⑪ Thermostatic Bi-metal Strip |
| ② Magnetic Element   | ⑦ Body or Housing of MCB | ⑫ Calibration Screw           |
| ③ Arc Chute Assembly | ⑧ Operating Mechanism    | ⑬ DIN Clip                    |
| ④ Terminal           | ⑨ Moving Contact         |                               |
| ⑤ Arc Runner         | ⑩ Arc Horn               |                               |

### Comply with Class 3 (MCB 63AF)

Shortens the cutoff time during a short circuit and suppresses ignitions and explosions

REFERENCE:



\*Circuit breakers of B-type and C-type up to and including 63A shall be classified into energy limiting classes in 1 or 3.





Safe and comfortable life  
Delivered by panasonic

## MCB Panel Boxes

### Features

- Clear cover that lets you check the MCB status easily
- Compliant with IP performance below  
IP40 : 2-36 Modules (Flush/Surface Mounted)  
IP20 : 1,1-2,3-4 Modules (Surface Mounted)
- Heat resistance up to 650°C
- Includes ground terminal with insulating cover
- Water level gauge that supports horizontal construction (16-36 Modules)
- Locked cover system Features



No. of Row	No. of Modules per Row	Capacity in 18mm Modules in Row	Flush Mounted	Surface Mounted
1	1	1	–	BQDT20101-PH
1	1-2	1-2	–	BQDT20201-PH
1	2	2	BQDT10211-PH	BQDT20211-PH
1	3-4	3-4	–	BQDT20401-PH
1	4	4	BQDT10411-PH	BQDT20411-PH
1	6	6	BQDT10611-PH	BQDT20611-PH
1	8	8	BQDT10811-PH	BQDT20811-PH
1	12	12	BQDT11211-PH	BQDT21211-PH
2	8	16	BQDT11611-PH	BQDT21611-PH
1	18	18	BQDT11811-PH	BQDT21811-PH
2	12	24	BQDT12411-PH	BQDT22411-PH
3	12	36	BQDT13611-PH	BQDT23611-PH




# SECURITY & COMFORT

## 1 Flame-retardant Material Urea Resin

Utilizing urea resin improves flame resistance and outstanding anti-tracking prevents electric shocks.

### Completely Insulated Construction



### Protection Against Electric shock

#### Enclosure Material Characteristics (Reference)


	Urea	PBT	Polycarbonate
Tracking Performance	Excellent	Good	Poor
Heat Deformation	Good	Good	Fair
Self-Extinguishment	Good	Good	Good




## 2 Durable & Smooth Operations Direct Driving Mechanism

Panasonic's proprietary method helps stabilizing the pressure applied to the contacts to ensure low heat and minimize the arc energy. This process reduces the risk of contact fuse and provides longer lasting resistance.

### Direct Driving Mechanism




### Seesaw Type of Switching System



## 3 Quick & Secure Connection Quick-Connect Terminal

These terminals improve site construction quality since fewer tightening screws are required, simplifying connections.

### Reduces the execution time considerably



### Tensile strength after connection

IEC60669-1 IEC60884-1 Standard Value	WIDE SERIES	SlimArt
IEC Standard	Wire	Strength
30N min.	1.5 mm <sup>2</sup> 4.0 mm <sup>2</sup>	30N min. or more


# EASY TO INSTALL

## Panasonic-designing one-touch action products that are easy to install.


The all On-Touch Action design concept that attaches devices to body plates and body plates to the cover plates makes the installation process easier than ever, saving both time & labor.

### Highly efficient, because of improvements in the utility box.

Sufficient space has been provided to house the connectors, and this has resulted in a higher efficiency than ever before.



### 1-TOUCH Construction











# VARIOUS TERMINALS AVAILABLE

We offer a wide range of terminals to suit the electrical cabling requirements of every country.

Panasonic has made available various terminals to suit the cabling environment anywhere in the world. With a structure which can be handled with more safety than ever before. Connections can be smoothly made, which leads to labor saving.

## Types of Electrical Cables and Terminals

Terminal	Quick Connect Terminal		Global Terminal	Pillar Terminal II
ICON	 Quick & Safety Solid Wire only 1.5-2.5mm <sup>2</sup>	 Screw-less Terminal Solid Wire: 1.5-2.5mm <sup>2</sup> Stranded Wire: 1.5-2.5mm <sup>2</sup>	 Solid Wire: 1.5-2.5mm <sup>2</sup> Stranded Wire: 1.5-2.5mm <sup>2</sup>	 Solid Wire: 1.5-4mm <sup>2</sup> Stranded Wire: 1.5-4mm <sup>2</sup>
APPLICABLE WIRE	 Solid OK	 Solid Stranded OK	 Solid Stranded OK	 Flexible OK

## Switches

- Designed for long service life (compliant with IEC standard) with 40,000 testing operations at 16A 250V~ full rating.
- Heat-resistant, highly conductive material used for the terminal plate reduces temperature increases in the terminal section.

### Terminal Section Temperature rise

IEC60669-1 Standard value		Conditions
Initial	45K max.	20A current
Use as 40,000 testing operations		16A current




## WORLDWIDE STANDARDS

### Safety design conforming to IEC standards

Switches conform to the IEC60669-1 standard(16A 250V~).  
Receptacles conform to the IEC60884-1 standard.  
All devices guarantee protection against electric shock and are designed for endurance, service longevity, and safety.

## Receptacles

- Wide receptacles secures insulation distance between contacts and external metal parts improving safety. (Compliant with IEC standard which requires insulation distance over 4.5 mm)
- Long-life design, capable of 10,000 strokes at 16A 250V ~ full rating.
- Heat-resistant, highly conductive material is used for the blade sockets and terminal point to reduce temperature increase.



### Terminal Section Temperature Rise

IEC60884-1 Standard value		Conditions
Initial	45K max.	20A current
After 10,000 Strokes		16A current

### Withdrawal Forces

IEC60884-1 Standard value		
After 10,000 Strokes	3 blades	54N max.
	2 blades	50N max.
	Single blades	2N min.

### Insulation Resistance

IEC60884-1 Standard value	
Initial	5M Ω min.
After 10,000 Strokes	

### Electric Strength

IEC60884-1 Standard value	
Initial	2,000V 1 min.
After 10,000 Strokes	1,500V 1 min.





# Earth Leakage Guard (GFCI)



## Features

- **Good for indoor & outdoor use**  
Applicable in places exposed to dust and water splash as bathroom, patio, rooftop terrace, pool area with pump, etc.
- **Fit with weatherproof cover with IP55**  
Weather proof cover shields against dust and water from all directions, which allows EL-Guard to be installed not only in the kitchen and bathroom, but also outside your home.
- **Required by the Philippines Electrical Code**  
The use of devices with ground fault protection is indicated in the PEC Article 2.10.1.8.



BATHROOM

PATIO

POOL SIDE

ROOFTOP TERRACE

## Line Up



WEGP1741SW9-PH



WEGP1741H9-PH



WEGP1741W9-PH



WEG8881K-PH



WEG8981K-PH



FIT FOR  
WEATHERPROOF  
COVER

## Weather Proof Plate



WEG7801

**IPX3**

Metal



WEG7901K-PH

**IP55**

Beige



WEG7901SWK-PH

**IP55**

Snow White



WEG7901HK-PH

**IP55**

Gray


	1-Gang 2-Device	1-Gang 3-Device
Metal	WEG7802	WEG7803
Beige	WEG7902K-PH	WEG7903K-PH
Snow White	WEG7902SWK-PH	WEG7903SWK-PH
Gray	WEG7902HK-PH	WEG7903HK-PH

## Weather Proof Cover Plate (Horizontal Type)



WEG8881K-PH

**IP55**  
Metal



WEG8981K-PH

**IP55**  
Plastic

## Weather Proof Plate for Receptacle Plug-In Type



WEG8991SW-PH

**NEW**

**IP55**

White




WEG8991LH-PH

**NEW**

**IP55**


Gray

## Normal System



10 Amperes IN = 10 Amperes OUT


## Leak System



10 Amperes IN ≠ 9.98 Amperes OUT  
(EL Guard will shut off)



## Ceiling-Mount Ventilating Fan




### Ways to improve Indoor Air Quality

The first step to improve indoor air quality should reduce or remove the source of the pollutants. Unfortunately, indoor pollutants are virtually impossible to eliminate completely, creating the need for a second step - ventilation. Ventilation is divided into "Natural Ventilation" and "Mechanical Ventilation".

Natural ventilation is neither consistent nor reliable since it relies heavily on wind and weather conditions. Mechanical ventilation removes stale, moist, polluted air, and replaces it with fresh outside air by using a fan.

### Continuous Ventilation


Sometimes referred to as general, central, whole-house or primary ventilation. Continuous ventilation is used to remove stale air and provide fresh air on a slow, continuous basis.



Enhance ventilation in the whole house to replace polluted air with fresh air by ventilation equipments.

### Intermittent Ventilation

Sometimes referred to as spot, local or secondary ventilation. Intermittent ventilation is used to capture and remove pollutant quickly at the source. This secondary process exhaust "bad air" from contaminated areas quickly, before it can spread throughout the house.



Enhance ventilation in specific part of a house.  
(e.g. bathroom, kitchen)



**SAFETY**  
Solutions




# 24-HOUR PROTECTION

with nanoe™ X + Comfort Cloud

Your health starts with you at home from the outside world. nanoe™ X with hydroxyl radicals contained in water helps families to ensure constantly clean and safe indoor environments by inhibiting bacteria, viruses, mold and other pollutants while deodorizing for clean and fresh air.

Choose Panasonic air conditioners equipped with nanoe™ X and stay connected by downloading the Panasonic Comfort Cloud App\* to manage your air conditioners with one device.



+



Comfort Cloud App  
(Air Connectivity)

\*A router with Internet connection is required to connect your air conditioner with the Panasonic Comfort Cloud App. The CZ-TAC61 accessory is required for PREMIUM INVERTER (3.0HP), DELUXE INVERTER and STANDARD INVERTER (1.0HP-2.5HP). Built-in Wireless LAN is only available for PREMIUM INVERTER (1.0HP-2.5HP).





# Stay Safe Indoors with 24-Hour nanoe™ X Air Protection<sup>1</sup>

nanoe™ X technology with the benefits of hydroxyl radicals can effectively inhibit adhered and airborne pollutants, and reduce odors. You can switch ON nanoe™ X mode with the air conditioning operation ON or OFF to actively clean your air when you are at home or operate independently when you are away from home.

nanoe™ X mode operates on low energy consumption and requires no maintenance – thanks to the titanium-made nanoe™ X device. nanoe™ X keeps you and your family safe indoors with 24-hour active air protection.



Switch nanoe™ X mode ON to inhibit pollutants and deodorise while you're away.

\*Energy consumption may vary depending on models.



Provides a cleaner and comfortable space for you and your loved ones.

## Smartify Your Air Conditioner Anytime, Anywhere


Take control of single or multiple air conditioning units wherever you are. Purify your home with the Panasonic Comfort Cloud App on your mobile device on-the-move.

### Purify On-The-Go



Switch on nanoe™ X mode without cooling while away from home.

### Control Single or Multiple Units




Convenient to monitor and manage the air conditioners with one mobile device.

<sup>1</sup>The nanoe™ X mode can be run independently from cooling mode, and needs to be ON for the 24-hour air purification to function.



## 7 Effects of nanoe™ X

nanoe™ X technology effectively inhibits 5 types of pollutants, deodorizes, and moisturizes with the benefits of hydroxyl radicals contained in water.



### Deodorizes Various Types of Odors




nanoe™ X reduces strong, adhesive odors<sup>1</sup> by deeply penetrating into fabrics, resulting in lasting freshness in your living space.

#### How nanoe™ X Reduces Odor



### Inhibits 5 Types of Pollutants



nanoe™ X inhibits airborne and adhered pollutants<sup>2</sup>, providing better air quality for your loved ones.

#### How nanoe™ X Inhibits Pollutants



PREMIUM

**INVERTER** Single-Split Type Air Conditioner

CS-XU9XKQ (Outdoor unit: CU-XU9AKQ)




Brave the new normal with care,  
thanks to nanoe™ X's 24-hour protection.



## PROTECTION THAT IS SCIENTIFICALLY PROVEN EFFECTIVE.


Ease out from your worries by ensuring that your living spaces are purified with Panasonic's air conditioners. Keep yourself and your family protected with the power of long-lasting nanoe™ X that produces hydroxyl radicals that inhibit \*2 \*3 both airborne and adhered viruses with 99.99%\*2 \*3 effectivity.



PREMIUM

**INVERTER** Window Type with nanoe™ X Technology

CW-XU1021VPH



nanoe™ X are nano-sized electrostatic atomized water particles with plentiful hydroxyl radicals.

Experimental results have proven the benefits of nanoe™ X generated by the nanoe™ X device with the cutting-edge nanoe-technology, generating 4.8 trillion hydroxyl radicals per second.





**SAFETY**  
Solutions



Brave the new normal and breathe healthy air with nanoe™ X, anywhere.

## Quality Air Solutions

### More than just fresh air for your health & beauty

Live comfortably with an Air Purifier that inhibits viruses, bacteria, and allergens over a wide coverage area for a healthier indoor air quality.

### Air Purifier

F-PXU70AWP



### Portable nanoe™ X Generator

F-GPT01A-K | F-GPT01A-R

#### ANTI-COVID-19 SOLUTION

**STAY SAFE  
AGAINST THE  
KILLER VIRUS\***

Using the Portable nanoe™ X Generator



nanoe™ X

Model	F-GPT01A
Applicable Volume	3m³
Air Volume	0.07 m³/min
Noise	34 dB
Consumption	3.5W
Power Cord	1.5m Type C USB
Voltage	DC 5V (Adaptor 1.5A above)
Dimension	170 x 90 x 66 mm (H) x (Top) x (Base)
Weight	0.4 kg
Color	Black, Red
Origin	Guangdong, China


#### Applications



\*testing done in a gauze saturated with SARS-CoV-2 virus solution was exposed to a nanoe™ X device from a distance of 15cm in a 45L box. The result is that over 99.99% of the activity of the SARS-CoV-2 virus was inhibited in 2 hours.

Note: This verification was designed to generate basic research data on the effects of nanoe™ X on the novel coronavirus in laboratory conditions. It was not designed to evaluate product performance.

#### How nanoe™ X Technology Works



The invisible hydroxyl (OH) radicals, amounting to 4.8 trillion/second, released by the device capture virus and bacteria floating in the air and turn them into water, effectively inhibiting them.

The value in Specification table are representative characteristics value at (\*1)230V/60Hz and (\*2)220V/60Hz




FV-15CSD115

# Ceiling Mount nanoe™ X Generator

## FV-15CSD1

- nanoe™ X Purification
- Silent Operation
- Low Power Consumption
- Easy Installation
- Contemporary Design
- Compact Size

### ■ Dimensions (unit: mm)



Purify the indoor air with the unique nanoe™ X technology by  
Air-e (nanoe™ X Generator)

### ■ Specifications

Rated Voltage [V]	Rated Frequency [Hz]	Power Consumption [W]	Air Volume [m³/h]	Noise [dB]	Net weight [kg]
230	60	4.0	16	25.5	1.1



- The value of air volume, power consumption and noise are specified at static pressure 0 Pa.
  - The value of air volume is the mean value and a tolerance of  $\pm 10\%$  is allowed.
  - The value of noise level is A weight average sound pressure level, the mean value is measured by our company. A tolerance of  $+3\text{dB}/-7\text{dB}$  is allowed. The noise is measured at 1m apart from the left, the front and the below of the product.
  - Condition for generating nanoe™ X
    - Room temperature : about  $5^{\circ}\text{C} \sim 40^{\circ}\text{C}$  (Dew point temperature more than  $2^{\circ}\text{C}$ )
    - Relative humidity : about  $30\% \sim 85\%$
- nanoe™ X is generated using the air in the room, and its amount is subject to the temperature and humidity.

### DISCLAIMER

- Data provided regarding the effectiveness of nanoe™ X have been obtained through experiments under special conditions using devices which generate electrostatic atomized water, and have not been tested through commercial products with the devices incorporated in them.
- Deodorization effect varies according to the environment (temperature and humidity), operation time, odor, and fabric types. It does not eliminate toxic substances in cigarettes (carbon monoxide, etc.). Odors that are continuously generated (e.g. building material odors and pet odors) are not completely eliminated. Results may vary based on usage, and seasonal/environmental variables (temperature and humidity). nanoe™ X inhibit activity or growth of viruses, but do not prevent infection.
- Individual results may vary based on usage, and environmental variables (temperature and humidity).



**SAFETY**  
Solutions

## Electric Bidet DL-EH10PH-W

# Better Personal Hygiene with Flexible Cleaning Modes

Panasonic's electric bidet is a great addition to your family, making toilet visits easier and simpler for everyday use. Great for those with limited mobility, such as senior citizens or people with disabilities. Also ideal for children who are starting toilet practices.

### Effortless & User-friendly



#### Easy to Operate

The simple icon design featured on the control panel can be understood and operated easily by users.



#### Dry & Clean Bathroom


With a built-in bidet, bathroom floors are less likely to become wet. A dry and clean bathroom can improve family members' overall safety by reducing the risk of slipping.



#### Hassle-free Cleaning

Minimizes the need for people with limited mobility, such as senior citizens, pregnant women, and people with disabilities to reach for the water hose for cleaning.

### Easy Installation



#### Compatible Toilet Bowl Shape

Shape Compatibility Check: Ensure your toilet bowl shape and dimensions match well with our bidet.



#### Toilet Bowl Dimension

Refer to this guide to easily check if your toilet is compatible with Panasonic's electric bidet. Ensure all measurements from A to D are within the same range.



#### Four Foot Rubbers

Ensure the four rubber feet align with the toilet bowl seat.





# Saving Solutions

Reduction on energy consumption through efficient products and systems.

## Applications

RESIDENTIAL

RESTAURANTS

SCHOOLS

OFFICES

HOSPITALS

STORES

FACTORIES

With our commitment for effective use of energy and reduction on power consumption, we have developed a range of products that contributes to the effective production and management of electricity suitable for every type of your projects.

## Key Factors



Applicable to new and renovation projects.




Maximum savings in less ROI duration.



Software based design for easy understanding.



**SAVINGS**  
Solutions



# ANCHOR

by **Panasonic**

AE14HXXXVHC10B

## 550W Mono Perc Module 144 Half-Cell Solar Panel

### Special Cell Design


10B technology decreases the distance between bus bars and finger grid line which is beneficial to power increase. Half-cell aims to eliminate the cell gap to increase module efficiency.

### Trust Anchor to Deliver Reliable Performance Over Time

- World-class manufacturer of crystalline silicon photovoltaic modules
- Rigorous quality control meeting the highest international standards: ISO 9001, ISO 14001 and ISO17025
- Regular independently checked production process from international accredited institute/company
- Tested for harsh environments (IEC 61701, IEC 62716)
- Long-term reliability tests
- 2 x 100% EL inspection ensuring defect-free modules

### Industry-leading Warranty based on nominal power

- 98% in the first year; thereafter, for years two (2) through twenty five (25), 0.55% maximum decrease from MODULE'S nominal power output per year, ending with the 84.8% in the 25th year after the defined WARRANTY STARTING DATE.
- Product Warranty is of 12 Years\*\*
- 25 year linear performance warranty



### IP68 Rated Junction Box

The IP 68 rated junction box ensures an outstanding waterproofing, supports installation in all orientations with less stress on the cables. Highly reliable performance with low resistance connectors ensures maximum output for higher energy production



#### High module conversion efficiency

Module efficiency up to 21.3 % achieved through advanced cell technology and manufacturing process



#### Anchor current sorting process

Up to 2 % power loss caused by current mismatch could be diminished by current sorting technique to maximize system power output



#### Excellent weak light performance

More power output in weak light condition, such as haze, clouds, early and late sun hours



#### Lower operating temperature

Lower operating temperature and temperature coefficient increases the power output



#### Extended wind and snow load tests

Module certified to withstand extreme wind (2400 Pascal) and snow loads (5400 Pascal) \*



#### Withstanding Harsh Environment

Reliable quality leads to better sustainability even in harsh environment like desert and coastal area





**SAVINGS**  
Solutions

## PRO iD Series

New generation luminaries with extremely efficient, smart, and safety design emitting a perfect seamless light.

### Caution for Risk of overtime use

Panasonic highly recommends to replace not only lamp tube, also lighting fixture in case of using more than 10 years.



Baselight	
	Long Lifetime 40,000 to 50,000 H
	High Efficacy 129-130lm/W
	Power Factor 0.95
	CRI 80
	Durability Body-Steel
Batten Type	
Reflector Type	
V-Shape Type	
Recessed Type (Width 300mm)	
Recessed Type (Width 150mm)	

Panasonic highly recommends to replace an existing fixture with lamp tube for LED fixture, which is Energy saving, long lifetime and safety designed. Especially PRO ID series has various types of shape for your requirements

### 2x2 Panel Light\_SP 2G



**120% UP**  
**30000 hours**

Improve and extend lifetime (30000 hours) for various usage

### BaseLight Low Temperature [Suitable for cold storage environment]




D Style	
Reflector	
I Style	

### Ex Splash Proof (2G)



Water proof (IP65) and high efficient fixture is suitable for area, such as parking lot, where use lighting for long period of time.

### LED Downlight



**Installation Friendly and Simple Design**

- Design of frame of the Downlight can fit with the ceiling for installation, that makes the finishing look flat even in case the ceiling is not flat.
- Simple and elegant design meet with any application

### LED Mini Flood Light



**IP65 Waterproof**

IP65 is recommended to be used for outdoor.

Input Power Voltage: AC220-240V  
Frequency: 50/60Hz  
Life time: 25000h  
Power Factor: 0.9  
IP: 65  
Material: Body: ADC12 (Black)  
Panel: Glass (Transparent)



**Reliable and Durable Design**



**Free Adjustment**

### LED Strip Light



Input Power Voltage: DC220-240V  
Lifetime: 20000h  
Dimensions: Width 11  
Length 50000  
Height 7

Material:  
Body: PVC





**SAVINGS**  
Solutions



## Floor Standing

S-24PB3Q6 | S-34PB3Q6/S-43PB3Q6/S-48PB3Q6

- Stylish design & powerful air flow
- The control panel/remote controller have nanoe™ X displays
- Compact 34,100 Btu ODU (210 mm shorter/27 kg lighter than current model)

[S-24PB3Q6  
Accessory]



[S-24PB3Q6  
Control Panel]



[S-34/43/48 PB3Q6  
Accessory]



[S-34/43/48 PB3Q6  
Control Panel]



## Clean airflow direction control with remote controller

Easily swing the louver at the touch of a button.



S-24PB3Q6 Blow distance: Up to 7 m

Push UP/DOWN



Push LEFT/RIGHT



S-34/43/48PB3Q6 Blow distance: Up to 11 m

UP/DOWN by  
Manual Setting



LEFT/RIGHT with  
a Button AIR SWING



## Other Functions

### Random auto restart


During a power failure, when power is restored, it automatically restarts operating in the same mode as just before power was lost.

### Auto fan mode

When the auto fan mode is set, the indoor unit of the air conditioner automatically is adjusted the suitable fan speed according to factors such as load.

### 12-hour On/Off delay setting timer

Pressing the timer button on the remote control lets you set operation start/stop time within 12 hours of the current time.



\* The images above show the remote controller screen display.

## Packaged Type Air Conditioners



**nanoeX**  
Generator Mark 2



**nanoeX**  
Generator Mark 2



**nanoeX**

### 4-WAY CASSETTE

- nanoe™ X technology
- Inverter • Smart Comfort w/ Conex (Common Panel: CZ-KPU3H)

### ADAPTIVE DUCTED

- nanoe™ X technology
- Inverter • Smart Comfort w/ Conex (Common Panel: CZ-RTC4)

### CEILING MOUNTED

- nanoe™ X technology
- Inverter • Smart Comfort w/ Conex

# Ceiling Fan

Optimizes air delivery while ensuring quiet, smooth operation with an elegant design that blends perfectly with your modern interior



SAVE  
UP TO  
**55%**  
ELECTRICITY

ENERGY SAVING  
**DC Motor**

COMPREHENSIVE  
**SAFETY FEATURES**

**1/f Yuragi**  
NATURAL BREEZE

**LED**



**F-60UFN**

- 4-Mode Brightness Selection
- 3D Blade delivers smooth & strong airflow
- Durable Blades (PPG Material)
- LCD Remote Control with 9-sequential speed selection
- 1-8 Hours On & Off Timer
- 2-8 Hours Sleep Timer




**F-48DFL**

- 3-Mode Brightness Selection
- 3D Blade delivers smooth and strong airflow
- Durable Blades (PPG Material)
- LCD Remote Control with 9-sequential speed selection
- 1-8 Hours On & Off Timer
- 2-8 Hours Sleep Timer



**F-60XDN**

- Sleek and smooth design
- 3D Blade delivers smooth and strong airflow
- Durable Blades (PPG Material)
- LCD Remote Control with 9-sequential speed selection
- 1-8 Hours On & Off Timer
- 2-8 Hours Sleep Timer



**F-60TDN**

- 3D Blade delivers smooth and strong airflow
- Durable Blades (PPG Material)
- LCD Remote Control with 9-sequential speed selection
- 1-8 Hours On & Off Timer
- 2-8 Hours Sleep Timer



**F-56XP6**

- Non-LCD remote control
- 3-Speed Selection
- 1,3 or 6-hour Off Timer
- 3 or 6 Hours Sleep Timer


## Advantages of DC Motor

**DC MOTOR IS UP TO 55% MORE ENERGY SAVINGS COMPARED TO AC MOTOR.**


- Lighter motor polarity where this process requires less electrical energy.
- Quite operation.
- More compact and half the size of AC motor

## DC Motor Technology

### Direct Current (DC Motor)




### Alternating Current (AC Motor)




## Safety Policy by Panasonic

The fan or its blade may dislodge due to following factors undermining the integrity of the unit.



**1**  
Worn out bolts



**2**  
Broken or damaged shaft

- Use of incompatible parts
- Use of non-original factory components
- Excessive wear and tear of fasteners

- Incorrect installation
- Material fatigue

## Safety Measure Application by Panasonic

### Cut-off Safety Switch

A cut-off safety switch is equipped to cease the power supply when dangerous wear & tear of the shaft and bolt are detected. If the abnormal wobbling continues, the lever will detach from the switch and the fan unit will detach. This will prevent further wear to the damaged part. It can also minimize parts fracturing to reduce the possibility of the fan unit to fall.


### Safety Wire

A special safety wire has been equipped to secure the fan motor to the ceiling hook which prevents it from falling off in the event that the fan motor detaches from the pipe rod.



### Current Fuse

During excessive current supply, the Current Fuse will cut off the power supply motor

These fans are equipped with **1/f YURAGI function** which is a fluctuating pattern that mimic natural and gentle breeze. With this sophisticated formula in varying air velocity and controlling wind force, these new ceiling fans gives you and comfortable feeling.



Incorporated with this human-concerned technology, this kind of rhythm maintains your external body temperature by giving you a feeling of natural wind when there is a change wind velocity



**LED** Model: F-60UFN

**4-Mode Brightness Selection**

<b>High Brightness</b>	<b>Medium Brightness</b>
<b>White</b>	<b>Cool Daylight</b>
<b>Medium Brightness</b>	<b>Low Brightness</b>
<b>Warm</b>	<b>Warm</b>

**85% Energy Saving**  
Compared to incandescent bulbs

**Handle-Free**  
No Bulb Replacement Needed  
With the long lifespan of LED light, there is no need to constantly change your light bulb, and reduce garbage waste.




# LED Dimmer Switch

## Features

- **Superior smooth control** from lower to higher adjustment  
Adjust the luminance level to minimum without flickering.
- **Minimum Brightness Adjustment Function**  
Adjust from 5% to 40% as the default for user.
- **Adequate LED capacity**  
Connect LED dimmable bulb without limitation within the wattage of rated capacity.


## Minimum Brightness Adjustment Function

The technician sets the minimum level as the default for user




Minimum Adjustment from 5 to 40%

Maximum Number of LED Dimmable Bulb for total 200W



The room is too dark or flickering appears  
Some bulb might not activate or is flickering at minimum.


Min [Not Activated]



Max

After adjustments

Min




Max

Minimum brightness can be adjusted if the following incidents happen


- Bulb is flickering : Increase the lower limit
- Too bright at minimum level : Decrease the lower limit
- Non equally brightness for each bulb : Increase the lower limit

① Remove Panel cover



Panel cover

② Adjust the knob to minimum position




Indicator lamp [Orange]  
Indicator will blink when the adjustment reach to minimum or maximum

③ Adjust the minimum brightness level by pressing the set up button

- ▲ Pressing the UP button will Increase the minimum level
- ▼ Pressing the Down button will Decrease the minimum level

① Adjust the knob to minimum position  
The minimum position



② Adjust the minimum brightness level by turning the minimum brightness setting knob.

※ Please use the screwdriver with a width of 3.5 ~ 4.0 mm, and rotating torque less than 0.4kgf · cm.

- ⊕ >> Turn the setting knob clockwise to Increase the minimum level
- ⊖ >> Turn the setting knob counterclockwise to decrease the minimum level.

### Precautions

Applicable incandescent lamps & low voltage halogen lamps & LED bulbs

- Chandelier lamp
- Silica lamp
- Clear lamp
- Hi-beam lamp
- Halogen lamp
- LED dimmable bulb

- When using low voltage halogen lamps, use an applicable transformer to convert voltage from 220 V ~ 240 V to 12 V.
- The brightness when dimmed is different depending on the LED bulb types and brand.
- When the knob is at lower limit, brightness is different depending on the LED bulb types and brand.
- Be sure to use a light bulb with a built-in fuse.  
Not doing so may result in damage to the dimmer switch when the light bulb burns out.




# VRF Air-Conditioner



## Low-Noise Operation

Numerous technological innovations, including an improved compressor and a newly designed bell mouth and larger fan, have dramatically reduced the outdoor noise level. The result is an even more comfortable building environment.



## Multiple large-capacity all inverter compressors (more than 14HP)

Two independently controlled inverter compressors achieve high efficiency. Redesigned components in the body provide performance improvement especially in the rated cooling condition and EER performance.



## Enlarged heat exchanger surface area with triple surface\*

The new heat exchanger features a triple-surface construction. Compared to the divided dual-surface construction in current models, there is no division of space and the area for heat exchange is larger. Also, highly efficient piping pattern increases heat exchange performance by 5%.

\*For 8 & 10HP unit, the heat exchanger is 2 row design.




FSV-EX Series / Exclusive Feature 1 /

## EXTENDED OPERATION RANGE UP TO 52°C

High reliability even under high temperature conditions

Designed to be durable enough to withstand extreme heat, FSV EX ensures reliable cooling operation over an extended operation range up to 52°C.

### OPERATING RANGE



## MAXIMUM 96HP FSV-MS3 Series



Connecting 4 units together in a single system allows maximum output of 96 HP

## A large number of indoor units can be connected

Up to 64 indoor units can be connected in a single system for ultimate design flexibility.

### Up to 64 Indoor Units Connectable\*




\*Maximum number of indoor units depends on outdoor unit capacity.

## FSV-EX Advantages

The most efficient, powerful and quiet system in Panasonic's history. There has never been a VRF system like it. It's the story of a true game changer.

### Extraordinary Energy-Saving Performance

The FSV-EX marks a revolutionary step forward in VRF efficiency. A look at the incredible EER value clearly indicates that. What's more, this high EER value is achieved even during part load operation. This shows the extraordinary energy-saving performance the FSV-EX is capable of providing.



### Extended Operation Range Up to 52°C

This FSV-EX can provide cooling even when the outside temperature reaches a maximum of about 52°C. And amazingly, it can still operate at 100% capacity when the outside temperature is as high as 43°C. This high power capability enables reliable operation even under extremely high temperature conditions.



LE1 Series  
**4.20\***  
EER  
\* In the case of 8HP

LE2 Series  
**5.08\***  
EER  
\* In the case of 4HP



**SAVINGS**  
Solutions



# Inverter Commercial Refrigerator/Freezer

[UPRIGHT TYPE & UNDER-COUNTER]




## High energy saving performance

- Inverter compressor
- Automatic frame heater duty optimization
- Automatic condensing fan speed control

### K series pull down speed image (refrigerator)

-Far exceeding strict Japanese industrial standard





## Advanced cooling performance to keep food freshness

**Refrigerator: -6 ~ -12°C**

**Freezer: -25 ~ -15°C**

- High pull down speed by strong cooling performance
- Slow down the speed of food deterioration
- Prevention of bacteria growing
- Suitable for storage of premium ice cream & frozen food

## The longer K series is used, the more cost & energy is saved




## "Panasonic Econavi" promotes energy saving further more

- Automatically "Econavi" optimizes energy saving operation with Panasonic original sensing technology.



**ECONAVI**



ECONAVI lamp will bright during ECONAVI ti



- Control condensing fan rotation speed
- Optimize frame heater duty
- Control compressor frequency







## Panasonic Inverter Condensing Units (8HP)



### Comparison of Operation Control; Inverter VS. Constant-rate



-Stabilization of suction pressure  
-Speed up of Pull Down  
=> Over 30% Energy Saving than Normal Machine

#### Wide range

Ambient temp :  $-15^{\circ}\text{C} \sim +43^{\circ}\text{C}$ 、  
Evaporating temp :  $-45^{\circ}\text{C} \sim -5^{\circ}\text{C}$  (8HP)


**High performance** : Big heat exchanger  
(Adopting sub cool system)

**Low noise** : Large size fan / Fan  
revolution control

**Data communication** : Low pressure auto shift,  
Sequential Defrost, etc.

**Energy Saving** : Over 30%

### Stabilization of suction pressure by output requirement prediction function




Suction Pressure Fluctuation of Normal machine



Suction Pressure Fluctuation of Inverter machine

**1/5**  
of  
constant-rate  
model















**SAVINGS**  
Solutions

# ONE SYSTEM THAT HOUSES ALL

Panasonic Multi-Split Air Conditioning  
System with R32 Refrigerant

Panasonic's Multi-Split Air Conditioning System with the environmentally friendly R32 refrigerant offers flexible multi-zone cooling solutions with just one outdoor unit, perfect for installation with limited outdoor spaces. Connects up to 4 rooms with independent indoor operational control and a vast selection of indoor types from a wide cooling capacity range. Enjoy a comfortable and cleaner living space with our customisable multi-split system.

Model	System 2	System 3	System 4	
	CU-2U18YBZ	CU-3U27YBZ	CU-4U28YBZ	CU-4U34YBZ
Capacity Range (kW) Rated (Min - Max)	 5.10 (1.50 - 6.10)	 7.50 (2.80 - 9.50)	 8.00 (2.80 - 10.20)	 9.50 (2.90 - 11.50)
Indoor Selection	 X-DELUXE INVERTER R32	 STANDARD INVERTER R32	 SLIM DUCTED	



## BENEFITS OF PANASONIC MULTI-SPLIT SYSTEM

Panasonic Multi-Split system offers installation versatility, independent control, space saving while maintaining great efficiency.




### VARIOUS COMBINATIONS FOR DIFFERENT NEEDS

Multiple types of indoor units are available for you to choose from based on your needs, preferences, and interior layouts. The various combinations of indoor units offer an ideal multi-zone cooling solution for your home.




### INDEPENDENT INDOOR UNIT OPERATIONAL CONTROL

Multiple indoor units are connected independently to the outdoor unit, enabling each indoor unit to be controlled separately.



### IDEAL SOLUTION FOR LIMITED SPACES

A tidier solution is to install only one outdoor unit rather than multiple outdoor units. This is great for residential buildings with limited outdoor unit installation.




### BETTER HEATDISPERSION TO MAINTAIN EFFICIENCY

Since the outdoor unit releases hot air out to the environment during the cooling operation, placing multiple outdoor units in a narrow space may cause overheating and potentially damage or shorten the lifespan of the outdoor units. Meanwhile, a single outdoor unit provides better air circulation and heat dispersion, while maintaining cooling performance and efficiency.

# ERV

## Energy Recovery Ventilator

Among various ways of achieving ventilation, the utilization of Energy Recovery Ventilator (ERV) is a modern and effective solution. In different aspects, ERV is able to bring more benefits, comparing to the traditional ventilation method.




1. Achieve Air Purification
2. Increase Comfort Level
3. Increase Energy Saving

## Air Purification



The Energy Recovery Ventilator draws fresh air from outside while stale indoor air is exhausted. With 24-hour continuous ventilation, Indoor Air Quality (IAQ) is enhanced by exhausting out harmful indoor air contaminants.

### Energy Recovery Ventilator Filter Structure



### MERV16 Filter


High-density purifying filter removal of particles as tiny as 0.3μm



Able to filter 0.3μm up to **≥95%\***

\*Tested by using MERV16 filter for model FV-35201, following ANSI/ASHRAE Standard 52.2-2017 (Testing Institution: Blue Heaven Technologies, Test report no. Z3-105-1)  
Recommended to change filter every 4-6 months and clean every month

### Diversion damper is equipped for Bypass Ventilation.



#### [ Heat Exchange Mode ]

- In heat exchange mode, it pre-cools the hot outdoor air before entering the house. Thus, energy is saved while providing fresh air.


#### [ Normal Ventilation Mode ]

- Bypass ventilation
- When outdoor air is highly polluted, it is not recommended to use bypass ventilation. It may cause negative pressure and polluted outdoor air may ingress into the houses through the gaps at the doors and windows.


When room airflow (RA) is greater than supply airflow (SA), it allows speedy exhaust of indoor polluted air. By using bypass ventilation during season change, it achieves better thermal comfort and energy savings.

## Comfort

### Office




### Residential




An Energy Recovery Ventilator employs energy recovery technology, which uses balanced airflows and recovers otherwise-expended total energy comprised of heat (sensible energy) and humidity (latent energy). Subsequently, less energy is needed for conditioning while maintaining high-level ventilation.

The newly developed Energy Recovery Ventilator can be interlocked with air conditioning system. It offers balance, humidity control and comfort. Indoor occupants get to enjoy fresh air currents while maintaining optimal temperature.

### Inside of Heat Exchange Core (diagram)



### Principle of Heat Exchange





**SAVINGS**  
Solutions

# Panasonic Power and Space Savings Multi-Split

Panasonic Multi-Split Outdoor is designed to produce increased cooling capacity indoors to accommodate large spaces. It is energy saving with its high energy efficiency by using the inverter technology and R32 refrigerant gas. The outdoor offers flexibility up to 11.50kW and up to 4 ports. It is equipped with chargeless gas for easy installation and is durable outdoors. The compact design and long piping provides greater installation flexibility for indoor units.

Connectable up to 2 indoor units



CU-2U18YBZ

Connectable up to 3 indoor units



CU-3U27YBZ

Connectable up to 4 indoor units



CU-4U28YBZ




CU-4U34YBZ



**COPPER TUBE  
CONDENSER**

## ENERGY EFFICIENCY



**Panasonic INVERTER technology**  
Quick Cooling and Constant Comfort



Panasonic-made  
microcomputer  
Unique & Precise



Panasonic-made  
compressor  
Gentle & Powerful



Panasonic air conditioners are equipped with the environmentally friendly R32 refrigerant which efficiently carries heat, leading to greater energy and cost-effectiveness with lower environmental impact.



Panasonic Inverter technology controls the temperature precisely to provide consistent cooling comfort while saving energy.

## WIDE COOLING CAPACITY RANGE

With maximum outdoor cooling capacity range of up to 11.50kW\*, a single outdoor unit can now be connected to indoor units of higher cooling capacity range, offering more flexibility to scale cooling operation according to different needs and preferences.

Outdoor unit	Outdoor Cooling Capacity kW Rated (min-max)	Max. indoor units combination
CU-2U18YBZ	5.10 (1.50 - 6.10)	8.5kW
CU-3U27YBZ	7.50 (2.80 - 9.50)	14.8kW
CU-4U28YBZ	8.0 (2.80 - 10.20)	16.2kW
CU-4U34YBZ	9.50 (2.90 - 11.50)	17.6kW

\*Up to 11.50kW apply to CU-4U34YBZ.

## INDOOR SELECTION

### X-DELUXE INVERTER R32

The X-Deluxe Inverter R32 comes with nanoe™ X air purification system to provide 24-hour nanoe™ X protection while AEROWINGS provides further and faster airflow. Comes with a built-in network adaptor that helps connect to the Panasonic Comfort Cloud App and gain remote access to control the air conditioning units anytime, anywhere.



CS-MPUL20KZ (6.0 kW) | CS-MPUL28KZ (7.1 kW)



CS-MPUL16KZ (2.8 kW) | CS-MPUL 2KZ (3.5 kW)  
| CS-MPUL BKZ (5.0 kW)



### STANDARD INVERTER R32

The Standard Inverter R32 series provides instant cooling upon start-up with POWERFUL Mode. For cooling comfort, AEROWINGS delivers further and faster airflow, while Big Flap directs cool air across the room. With an optional network adaptor, you can control the air conditioning units with the Panasonic Comfort Cloud App anytime, anywhere.



CS-MPUL20KZ (6.0 kW) | CS-MPUL28KZ (7.1 kW)



CS-MPUL16KZ (2.8 kW) | CS-MPUL 2KZ (3.5 kW)  
| CS-MPUL BKZ (5.0 kW)



### SLIM DUCTED

Featuring slim and compact design with built-in drain pump for flexible installation in narrow ceiling spaces. Cool airflow is directed towards the ceiling over a wide-angle range. With an optional network adaptor (CZ-TACG1), connect air conditioning units to Panasonic Comfort Cloud App for a convenient control anytime, anywhere.



CS-MU10D3Z (2.8 kW) | CS-MU 2KZ (3.5 kW) |  
CS-MU BKZ (5.0 kW) | CS-MU20D3Z (6.0 kW)







**SAVINGS**  
Solutions

# ECONAVI

Detects Inefficiencies and Saves Energy

# ECONAVI



**In the morning**  
Thorough cooling when there is a high level of activity



**In the afternoon**  
Reduced cooling when there are fewer people



**At night**  
Automatic Thermo Off depending on conditions at the end of the day\*



**DETECTION OF LEVEL OF ACTIVITY ENABLES PRECISE POWER SAVING.**

Presence or absence of people at their desks and the level of activity in the office are detected in real time. Set temperature is automatically adjusted to optimise the lower power consumption.

## Human activity and presence detection

Activity detection		Presence detection	
HIGHER ACTIVITY	LOWER ACTIVITY	After 20 mins absence	After 3 hours absence
Cooling Set Temp. +/-0°C	Cooling Set Temp. +1°C	Cooling Set Temp. +2°C	Cooling Thermo OFF*
Heating Set Temp. -1°C	Heating Set Temp. +/-0 °C	Heating Set Temp. -2°C	Heating Thermo OFF*
Every 2 min	Every 2 min	After 3 hours the setting can change to Stop or Temperature Shift	

\*Depending on conditions, the setting can change to Switch Off After 3 Hours, Thermo Off or Temperature Shift.



**SAVINGS**  
Solutions


# ECONAVI



## Remote ECONAVI sensor allows optimum energy operation

Pillars, walls, cabinets, and other fittings obstruct the sensor, reducing the area of detection and lowering the energy-saving effect. Taking into consideration blind spots, Panasonic enables the optimum layout for sensors in any office.

### Wide detection area



A sensor is remotely set to maximize the detection area.

Installation flexibility ready for indoor unit replacement and layout changes.




ECONAVI sensor  
**CZ-CENSC1**

**Panasonic enables use with various types of indoor units**

Providing outstanding energy-saving performance, Panasonic's inverter VRF System can be connected to ECONAVI to detect when energy is being wasted. ECONAVI senses the presence or absence of people and the level of activity in each area of an office. When unnecessary heating or cooling is detected, indoor units are individually controlled to match office conditions for energy-saving operation.

## ECONAVI VRF Field Test



- Indoor units (12)
- Sensors (12)

- Trial term: 11 Apr - 16 May 2014
- Location: Panasonic Malaysia Building
- Office floor: Cooling capacity 112kW
- Testing conditions:
  - Remote controller setting temperature 23°C
  - Setting time AM7:00-PM21:00
- Units used

System	Outdoor unit	Indoor unit
① CU-L7-6	U-20ME1E8	1 S-106MU1E5
		2 S-106MU1E5
		3 S-106MU1E5
		4 S-106MU1E5
② CU-L7-7	U-20ME1E8	5 S-56MU1E5
		6 S-106MU1E5
		7 S-106MU1E5
		8 S-56MU1E5
③ CU-L7-7	U-14ME1E8	9 S-106MU1E5
		10 S-106MU1E5
		11 S-56MU1E5
		12 S-106MU1E5



Panasonic Malaysia Building



Outdoor units on the roof



Sensor installation example

Interior of the office

### Power consumption

Without ECONAVI

With ECONAVI

Up to **15%**  
energy saving

Energy-saving effect  
tested and verified  
by Field test



# Security Solutions

Monitor and secure your properties from any unwanted incidents.

## Applications

RESIDENTIAL

RESTAURANTS

SCHOOLS

OFFICES

HOSPITALS

STORES

FACTORIES

Security has always been a top priority to every project developments and we at Panasonic, take this aspect seriously by developing products and systems that has technological advantage and key features that are first in the market and has a proven a track of project references worldwide.

## Key Factors



Applicable to new and renovation projects.



Technological features addressing current property security issues.



Requires low maintenance.





## Slim Smoke & Voice Alarm

Provides prompt notification  
in the event of a fire.

### Clear and easy-to-understand "alarm voice" and a long-life battery of up to 10 years

Approx. 87 dB at 1m distance from equipment  
(at peak value)(measured by our company  
based on corporate judgment standard)  
For alarm sound "Whiz, whiz," a wide frequency  
band from 0.3 kHz to 4.0 kHz is adopted for  
easy catching even by old people and children.  
The battery lasts up to 10 years.




### SH28455911

Smoke alarm for  
residential use



### Immediately understands what happened.



Model No.		SH28455911
Power Supply		Dedicated Lithium Battery (3V)×1
Battery Life		Approximately 10 years(*)
Detecting Method		Smoke Type (Photoelectric Method)
Class		Type2
Alarm Sound/ Voice Alarm	Fire	Whiz, whiz, fire, fire!
	Low Battery	"Blip, Low Battery!" × 3 times. "Blip, approx. every 40 seconds after that.
	Trouble	"Blip, blip, blip, Problem, Please check" × 3 times. "Blip, blip, blip," approx. every 40 seconds after that.
Alarm Volume		84 dB or more at 1 m distance from equipment
Dimension		Approx. Ø100 mm × 44 mm (including attachment base)
Weight (Including Dedicated Lithium Battery)		Approx. 140g.
Operating Temperature		0°C to + 50°C
Installation Location		Ceiling/Wall Surface

Signal Transmission Contact (No-Voltage)	—
---	---





\*It may be shorter depending on usage environment.

	Mode	Voice Alarm	Indication
Function	Normal	—	OFF
	Alarm	Whiz Whiz Fire Fire	Blink
	Silent	—	OFF
	Trouble #1	Blip, Blip, Blip, Problem please check	Blink
	Trouble (Silent)	—	Blink
	Low Battery #2	Blip, Low Battery	Blink every 8 seconds
	Low Battery (Silent)	—	Blink every 8 seconds

# Autodoor System

Safety | Construction | Reliability | Multifunction



Motor	Controller	Sensor	Specifications																																																																																										
			<table><tr><th>Model of the door</th><td colspan="2">Single door</td><td colspan="2">Double doors</td><td colspan="2">Single door</td><td colspan="2">Double doors</td></tr><tr><th>weight</th><td colspan="2">I less than 120kg</td><td colspan="2">I less than 120kg*2</td><td colspan="2">I less than 150kg</td><td colspan="2">I less than 150kg*2</td></tr><tr><th>Width</th><td colspan="8">Door width 600~1250mm</td></tr><tr><th>Installation method</th><td>exposed</td><td>concealed</td><td>exposed</td><td>concealed</td><td>exposed</td><td>concealed</td><td>exposed</td><td>concealed</td></tr><tr><th>Opening speed</th><td colspan="2">14-11cm/s (remote control, adjustable)</td><td colspan="2">14-40cm/s (remote control, adjustable)</td><td colspan="2">14-11cm/s (remote control, adjustable)</td><td colspan="2">14-34cm/s (remote control, adjustable)</td></tr><tr><th>Closing speed</th><td colspan="2">10-40cm/s (remote control, adjustable)</td><td colspan="2">10-38cm/s (remote control, adjustable)</td><td colspan="2">10-39cm/s (remote control, adjustable)</td><td colspan="2">10-34m/s (remote control, adjustable)</td></tr><tr><th>Open duration</th><td colspan="4">0-9s</td><td colspan="4">0-9s</td></tr><tr><th>Manual opening force in case of power failure</th><td colspan="2">46.0N(4.7kgf)</td><td colspan="2">61.7N(6.3kgf)</td><td colspan="2">63.7N(6.5kgf)</td><td colspan="2">89.2N(9.1kgf)</td></tr><tr><th>Ambient temperature</th><td colspan="4">-20℃~+50℃</td><td colspan="4">-20℃~+50℃</td></tr><tr><th>voltage</th><td colspan="4">AC 200~250V 50/60Hz</td><td colspan="4">AC 200~250V 50/60Hz</td></tr></table>	Model of the door	Single door		Double doors		Single door		Double doors		weight	I less than 120kg		I less than 120kg*2		I less than 150kg		I less than 150kg*2		Width	Door width 600~1250mm								Installation method	exposed	concealed	exposed	concealed	exposed	concealed	exposed	concealed	Opening speed	14-11cm/s (remote control, adjustable)		14-40cm/s (remote control, adjustable)		14-11cm/s (remote control, adjustable)		14-34cm/s (remote control, adjustable)		Closing speed	10-40cm/s (remote control, adjustable)		10-38cm/s (remote control, adjustable)		10-39cm/s (remote control, adjustable)		10-34m/s (remote control, adjustable)		Open duration	0-9s				0-9s				Manual opening force in case of power failure	46.0N(4.7kgf)		61.7N(6.3kgf)		63.7N(6.5kgf)		89.2N(9.1kgf)		Ambient temperature	-20℃~+50℃				-20℃~+50℃				voltage	AC 200~250V 50/60Hz				AC 200~250V 50/60Hz			
Model of the door	Single door			Double doors		Single door		Double doors																																																																																					
weight	I less than 120kg			I less than 120kg*2		I less than 150kg		I less than 150kg*2																																																																																					
Width	Door width 600~1250mm																																																																																												
Installation method	exposed	concealed		exposed	concealed	exposed	concealed	exposed	concealed																																																																																				
Opening speed	14-11cm/s (remote control, adjustable)			14-40cm/s (remote control, adjustable)		14-11cm/s (remote control, adjustable)		14-34cm/s (remote control, adjustable)																																																																																					
Closing speed	10-40cm/s (remote control, adjustable)			10-38cm/s (remote control, adjustable)		10-39cm/s (remote control, adjustable)		10-34m/s (remote control, adjustable)																																																																																					
Open duration	0-9s				0-9s																																																																																								
Manual opening force in case of power failure	46.0N(4.7kgf)			61.7N(6.3kgf)		63.7N(6.5kgf)		89.2N(9.1kgf)																																																																																					
Ambient temperature	-20℃~+50℃				-20℃~+50℃																																																																																								
voltage	AC 200~250V 50/60Hz				AC 200~250V 50/60Hz																																																																																								
DC brushless motor with small volume and large power is used to accommodate deceleration of the high-speed gear box system with high transmission efficiency and small noise and then to drive the belt. A safety device is equipped inside. Despite of frequent switch on and off, it can run continuously without fault. The motor transmission belt pulley is made of metal and free from maintenance.	The controller module accepts inspection signals from the sensors or other signal switches drive the motor and control the door to run in an appropriate way. Two groups of aid light ray sensor interface and aid function interface are increased to further improve safety and multifunction of the product.	<ul style="list-style-type: none"><li>• Operation Safer because of big sensing range and small blind area.</li><li>• Using the latest digital signal processing, with the static detection function.</li><li>• Adjustment easier, it can be adjusted flexibly according to the premises.</li></ul> 																																																																																											


## Door Closer Series

### Long life

- Precise sealed, preventing oil leakage.
- High quality die-casting aluminum to ensure the useful time is more than 500,000 times.
- 180 degree hydraulic control.
- Two stage speed adjustment.


### Super quiet

- To build the world's most advanced mute positioning device, the sliding arm introduced into imported spring piece.



*Elegance In Style*

**Sophisticated Manufacturing**  
**Stable Solid**



## Hinge Series

- Panasonic hinge series have excellent material and fine grinding
- They run smoothly without noise, they are durable and easy to install
- Suiting to various kinds of wooden doors and metal doors

## Lock Series

- Meet the **GB 21558-2008/ ENEN 12200-2003** Standard
- Latch can be used more than **500,000 times**
- Surface parts are made of SUS304 stainless steel
- Security design, prevent the screws from being unloaded outside
- Stability design, prevent the handle loosening
- Latch can be turned, it's easily used for both left-opened and right-opened door
- With white Copper keys



*Refine Manufacturing*

## Functional Components

### Electric lock



- The door will be locked when closed; the delay time can be adjustable from 0s to 9s.
- When the door opens, the lock will be automatically unlocked, and the delay time is 1s.
- Once the switch signal is inputted, access control unit and the remote control are to be connected.
- The technology and development of the lock aims at dealing with various running status of the auto-door.
- The stable performance preventing the possibilities of malfunctions
- The photosynthetic conjunction it possesses can achieve automatic lock if the door remains closed in 5 seconds.



## Access control unit

### • Technical parameters

- ① Operating voltage : 12V
- ② Operating current : 110mA
- ③ Operating temperature : -20°C ~ 60°C

### • 4 models of opening:

- ① Use the password (4-digit)
- ② Use the magcard
- ③ Use both the magcard and the 4-digit password
- ④ Use the magcard or the password

### • Features

- ① Up to 1000 magcards are acceptable. And the stored information is still remained even if the power failure.
- ② The noctilucant keyboards are made of stainless steel, which is waterproof and vandal-resistant. Magnetic card has long induction distance and high sensitivity.
- ③ 2 groups of indicator lights (power and induction lights).
- ④ The new circuit board and control program design enrich the functions.



## Remote control

### • Features

- ① The dual-code technology can effectively avoid signal interference. More secure.
- ② The new designed circuit board and control program improve its stable performance. More accuracy in sending and receiving signals economizes the electricity of remote control, and extending the operation time effectively. The new design to ensure the remote control distance and the sensitivity.
- ③ The new added selection model can make the auto door automatically opens or closes when the door unlocked.



### • Technical parameters:

Operating voltage	12V+0.5V	Operating current	< 7mA
Operating temperature	-25°C~65°C	Receiving sensitivity	-100dBm
Operating frequency	315MHZ	Output current	<10A

### • Product introduction:

#### ① Multi-function :

Realizing four kinds of operating status, such as the auto door normal open, normal close, normal switch and access control.

Realizing the linkage action with the access control system and the electrical lock.

#### ② Professional :

Combine with the market demand, and developed specially for automatic doors.

The stable performance preventing the possibilities of malfunctions

#### ③ Convenience :

Convenient by the long remote control distance.

The compact size makes it easy to install.



## Wireless press switch:

The new improved wireless press switch, which is composed of signal receiving device (NACS-CMJ200) and signal transmitting device (NACS-CMF200), is specifically developed for auto doors. What you should do is just to reconcile the code on both the signal receiving device and the signal transmitting device since the intelligent matching function in debugging.

### • Signal receiving device:

It is easy to connect and adjust intelligently.

The control signal can be adjusted during 1~10s.

At the same time, the -100dBm high sensitive signal receiving can ensure the door operation more smoothly.



### • Signal transmitting device:

Energy saving. Only 2 AAA batteries are needed for operating. There is a prompt function when lack of electricity. The luxury and beauty silver-gray surface and the arc angular design, makes is has comfortable feel.

## Contactless switch:

- Use the photoemission techniques to achieve the non-touch detection; the detection distance is adjustable within 300mm.
- It can avoid the cross-infection caused by the hand and elbow touch, to ensure the absolute hygiene. And it is particularly suitable for clean room, sterilization room, operating room, as well as food processing factory, pharmaceutical industry, chemical industry and other entrances.
- The unique protection structure makes it has waterproof function.
- The sensor is designed with infrared LED spotlights, which is not affected by the dust and dirt.
- Base on the elegant and compact design, the product can be embedded in various wall (except within the metal wall)







# Fire Alarm Systems

EBL512G3 AND EBL128



EBL ONE Control and



EBL512G3 Control and  
Indication Equipment (5000)

## General

EBL512G3 and EBL ONE are analog addressable fire alarm systems which can also be used with addressable detectors, inputs and outputs as well as with conventional detectors. Both fulfill the EN54 standards: EN54 part 2 (Control and indicating equipment) and EN54 part 4 (Power Supply). Detectors, manual call points, and general input and output units for free programmable customer specific functions can be connected to the COM loops. Each loop unit uses one address.

## INTEGRATED, INTELLIGENT PROTECTION

**Fire is just one of the physical risks to your business. With Panasonic, you have the option to integrate your fire detection technology into wider solutions, providing seamless, more comprehensive security and monitoring.**

Combine our fire alarms with our market-leading security surveillance systems and you benefit from the reassurance of having proven, ultra-reliable technology at work throughout your premises. Our expandable, interoperable systems deliver greater value, reduce workloads and improve effectiveness, creating flexible, intelligent industrial all-round protection systems in every professional setting.

Using the WEB-server module, we can connect the fire alarm system via TCP/IP with CCVE monitoring software, the WV-ASM200, and also with CCVE IP virtual matrix, the WV-ASC970/ASM970. This interoperability between both systems makes life easier for the operator by linking the fire and fault alarms from the control panel with the live and playback video from the cameras and recorders. This allows the operator to realize the situation in real time from the control room enabling them to take action quickly and safely. In addition, both CCVE monitoring systems (WV-ASM200 and WV-ASM970) provide a map window where all the fire detector icons can be added. This allows security personnel to easily check the status of all the detectors, which blink when there is an alarm.





**SECURITY**  
Solutions



### NDA A Compliant Devices

## i-PRO NETWORK PRODUCTS

i-PRO cameras are designed for multiple applications and provide a wide range of capabilities, including Enhanced Super Dynamic, High-accuracy Motion Detection, Analytic features, Face Detection, Wide-area Monitoring, and more.

### PTZ Cameras

i-PRO PTZ cameras combine unparalleled image quality with incredible durability and reliability. The perfect security camera for wide-area coverage requiring pan, tilt and zoom capability.



### Multi Sensor Cameras

i-PRO multi-sensor cameras capture the highest quality images even in very challenging dynamic environments. These cameras can excel at capturing clear images, even in low light conditions from multiple angles through the use of their four repositionable lenses.

### Dome Cameras

i-PRO fixed dome cameras have the power to be more discreet than standard fixed network cameras. i-PRO fixed dome cameras work well in busy open areas since they can conceal which direction they are pointing while still providing excellent and reliable video.



### Bullet/Box Cameras

i-PRO fixed box bullet/box cameras provide a clearly visible, fixed angle of view, making it easy to see exactly where they're pointing and record a precisely defined area.

### 360 Degree Cameras

i-PRO vandal resistant 360° dome cameras are ideal for surveillance application where wide area coverage is required. This type of camera allows for multiple viewing angles and can be used to improve area management as well as detect activities in a large area.





# Video Intercom System

VL-MC3000BX | VL-PC3400BX | VL-PC3800BX | VL-VC3900BX | VL-VC3500BX



PSU VL-PC3400BX



Room Monitor VL-MC3000BX



Door Station  
VL-VC3500BX



Lobby Station  
VL-VC3900BX



Power Distributor  
VL-PC3800BX



Guard Station  
VL-GC3700BX

## Safe, Secure and Convenient Living



### Greet Visitors Anytime, Anywhere

The Smartphone Connect feature connects mobile devices to the system so homeowners can receive guests anytime, anywhere. Answer guests in real-time through the smartphone whether you're inside or outside your home.



### Additional Security with SOS One Touch

Security measure that connects residents to the guard station with just one push of the button in case of a break-in or other emergencies.

\*Up to 8 slots can be used to link 3rd party devices (SOS buttons and sensors) to the IP video intercom system.



### Safe and Quick Contactless Entry


Residents simply need to send a QR code to their invited guests or deliveries in advance, so they can directly go to the unit's front door.



### Security Detection for Home Safety

The integration can be connected to the room monitor to detect emergencies such as fire, smoke, and break-ins. Upon detection, an alarm will be sent to the guard stations simultaneously.

\*Up to 8 slots can be used to link 3rd party devices (SOS buttons and sensors) to the IP video intercom system.



### All-day Surveillance through Smartphone

Internet protocol (IP) cameras can provide live view videos of public spaces such as the lobby, car parking, and recreational areas for security purposes. Residents will be able to access via room monitor and smartphones anytime, anywhere.

\*Up to 100 Internet protocol (IP) cameras can be integrated with IP video intercom system.

### Elevator Ride Made Convenient and Easy



Contactless Guide to  
Your Guests and Deliveries



On-time Departure  
At Your Convenience





# Comfort Solutions

Achieve better lifestyle upgrades with products that improves your well being.

## Applications

RESIDENTIAL

HOTEL

HOSPITALS

SCHOOLS

True to our commitment of providing a better life, we have developed a range of products from personal care to dwelling necessities providing wellness to your daily living.

## Key Factors



Applicable to new and renovation projects.



Products ranges from personal care to home improvements



Built in additional features for savings and safety


# Panasonic Hotel TV

## LED TV TH-65LX800X

See it all. Feel it all.



androidtv




### Get more from your TV

Simplify your entertainment experience with Android TV and discover 400,000+ movies and shows in one place.



### Watch what you love, control it with your voice

Do more on your TV with your voice. Press the Google Assistant button on your remote to quickly search 400,000+ movies and shows, get recommendations to match your mood, control smart home devices, and more.



### Optimal brightness and colors – whatever the source

Multi HDR Format - By supporting all HDR (High Dynamic Range) formats our TVs assure best possible performance - regardless of picture source. Brightness and colors are optimised scene-by-scene; whether the source is Dolby Vision, HLG, HDR10 or the HDR10+ format.



**COMFORT**  
Solutions

## Bathroom Water Heater DH-6SM1PW



No fails, only safe and easy shower with  
**Japan Quality Water Heater**

- 6.0 kW
- Compact body for quick and easy installation
- Operate at Low Pressure
- Better Temperature Control

### 9 Safety Points

Fully equipped with safety features  
for user's protection.





# Hair Dryer

EH-NA98-K605

Total care for hair,  
scalp and skin



Moisture-rich nanoe™ moisturises hair and scalp, while nanoe™ & Double Mineral Ions prevent damage from brushing and protect from UV rays. It comes with four special modes for hair, scalp, and skin.



nanoe™



Double mineral ion



Hot/Cold  
alternating mode



Intelligent temperature  
control mode



3 airflow settings




Scalp & Skin  
mode



## Reduces hair damage over time

Panasonic's advanced hair dryer is designed to have the combination of nanoe™ and Double Mineral technology to reduce hair damage over time. Use it to lock in moisture, reduce frizz, and protect your hair's shine by tightening the cuticle, making your hair look healthier and preventing damage from UV rays.



## Reduction in split ends

To combat hair damage, moisture-rich nanoe™ penetrate the hair, while Double Mineral increase cuticle cohesion - taming the tips so they are less prone to splitting. The result is reduction in split ends from 32% to 6% over time, for that healthy-looking hair you've always dreamed of.

\*Test result by SGS



**COMFORT**  
Solutions



## Electric Iron

### NI-M250T

**It's time to straighten this out! Choose ironing made easy and fun.**

Enjoy the benefits of a steamer and a dry iron enhanced with innovative design and functionality. Panasonic's electric steam irons effectively press flat against your clothes, while using little jets of steam to really iron wrinkles out of your clothes.



#### Powerful steam removes stubborn wrinkles

Spraying out up to 15 g/min. of steam, effectively smooths out creases. In addition, push the button and the Power Shot function creates a powerful burst of steam which goes deep into the garment and is helpful for removing stubborn wrinkles.



#### Remove wrinkles from hanging garments

Vertical shot directs a full burst of steam to smooth out and remove wrinkles from hanging garments, curtains, drapes and more.



#### Tough & Smooth Ironing

Advanced Titanium Coated Soleplate slides easily and stands up to long-nose. The smoothness of movement has increased by 20% <sup>\*1,\*2</sup> and anti-scratch performance has been improved by 4 stages (from 2H to 6H) <sup>\*2,\*3</sup>

<sup>\*1</sup> The effort needed to move a hot iron (measured on a cotton fabric).

<sup>\*2</sup> Tested with a pencil hardness test.

<sup>\*3</sup> In-house comparison with the Panasonic P Series.



**COMFORT**  
Solutions

# Cordless Stick Vacuum Cleaner

**MODEL MC-SB53K**

**Tangle-free,  
easy maintenance**



Made in  
JAPAN



## Tangle-free Power Nozzle




Firmly captures hair from the floor. Transfers it to the thinner ends and sucks it in the

## Float-lite Technology



Nozzle can be moved freely in 360° makes cleaning easier with less strain.

## House Dust Sensor



Detects invisible microscopic particles like bacteria, pollen, and mold.

## Fuss-Free Cleaning



Removes pet fur from floors and furniture without tangling.

**MODEL MC-SBM20**

## Lightweight Easy Clean Routine

### Lightweight & Easy to Handle



The light 1.6 kg weight makes flooring, high places, stairs, narrow spaces, and underneath the furniture easy and effortless to clean.

### Powerful Cleaning in Every Corner



The nozzle reaches right up to walls to capture dust in every corner with 70 W of suction power for a thorough cleaning.

### Versatile Cleaning Everywhere



Various attachments make cleaning easier.






# Professional Microwave Oven NE-1853

## Reliability

### Reliability in "Heavy Use"

PMWO Usage per day <sup>\*(2)</sup>



Average customers use one PMWO about 50 times per day. The durability for heavy use is obviously very important. Left images are some of the tests that we carry out to ensure that our ovens can work efficiently in this environment.

<sup>\*(1)</sup>This test is to study the design of our products in our testing room, and this information is not to guarantee the products quality in those situation all time.

<sup>\*(2)</sup>This data is the average of the market survey made by KABO.



**Door open and close endurance test <sup>\*(1)</sup>**  
Door open and close 400K times



**Intermittent operation endurance test <sup>\*(1)</sup>**  
On(60sec) and Off(30 sec), 200K times  
On(20sec) and Off(10 sec), 200K times



**Control panel endurance test <sup>\*(1)</sup>**  
Operating the key pads 200K times

### Reliability in EMC requirement

#### Accreditation, Authorization, Filing, Registration.

Electromagnetic Compatibility(EMC) is one of the most important issues facing the industry today. Panasonic Corporation have "Panasonic Corporation Analysis Center EMC Test Laboratory" in Japan, which is operated in accordance with our internal standard procedure/Quality System in compliance with ISO/IEC 17025.

#### Panasonic Corporation Analysis Center EMC Test Laboratory

Located in an area for precise testing without any interference from outside electromagnetic.



KABO: Kitchen Appliances Business Division  
PMWO: Professional Microwave Oven

Europe




TUV SUD Product Service Certification No: JPN1012A

Japan



Japan Accreditation Board (JAB) JAB Code: RTL02730

Anechoic chamber



Open Test site (3m/10m/30m)



All evaluation testing engineers are certified as qualified Electromagnetic Compatibility Engineer by the National Association of Radio and Telecommunications Engineers, Inc. (USA)





## 1 Door | Direct Cool Non-Inverter NR-AQ151NS Single Door Refrigerator



## Modern and Trendy Flat Door Design Environment-Friendly, Energy Saving and Efficient Cooling

Product Dimension(WxDxH) : 540 x 600 x 997 mm  
Capacity : 5.2 cu ft (148 L)  
Weight : 27 kg



## MAJOR KEY FEATURES

- 1 Modern & Trendy Flat Door Design
- 2 Environment - Friendly
- 3 Energy Saving & Efficient Cooling

## 2-Door Top Freezer No-Frost Deluxe Refrigerator NR-BP272VD



**5-STAR ENERGY EFFICIENCY**  
REFRIGERATOR-FREEZER



**PRIME COOLING +**



## Energy Efficient Food Storage with Superior Freshness

The No Frost Deluxe Refrigerator gives you superior energy savings while enjoying long lasting freshness.



**SUPERIOR ENERGY SAVINGS**




## 5-star energy rating with intelligent inverter

Powered with High Efficiency Inverter Compressor and AI ECONAVI.

AI ECONAVI sensors detect and microprocessor analyze the usage conditions optimizing the cooling performance.




# Features



## 5-Star Refrigerator-Freezer Category

Experience more efficient cooling with its -18°C Freezer compartment that passed testing conditions with 5-Star Refrigerator-Freezer category rating.



## Hygienic Food Storage, Safe from Bacteria and Odors.

The Ag Filter deactivates 99.99%\* of bacteria and reduces unpleasant odors for a more hygienic food storage.

\*Certified by Broken Quality Evaluation Institute Test Report number: No. 20215058561-1



## Jumbo Freezer for Bulk Buyers

The large-capacity freezer lets you buy in bulk without worries on the storage space.



## Superior Cooling for Everyday Freshness

The Prime+ Cooling compartment maintains freshness for a longer period of time without freezing.



## Long-Lasting Freshness for Fruits and Vegetables

The Fresh Safe compartment keeps the optimum humidity and constant temperature to retain freshness and moisture, making it an ideal storage for fruits and vegetables.

